


WESTERN STAR 48X



CONFIGURA	ATIONS	
STANDARD	6 X 4 SINGLE STEER	
GCM		
UP TO 130 TO	NNE GCM*	
SUBJE	GCM RATINGS AVAILAB CT TO APPLICATION AND INEERING APPROVAL.	
DESCRIPTION	N	ММ
BA - BUMPER	TO AXLE	
Bumper to axle		765
BBC - BUMPE	R TO BACK OF CAB	
Day cab		2,865
36" sleeper		3,565
48" sleeper		3,865
60" sleeper		4,165
RRF - REAR FI	RAME HEIGHT - UNLADEN	1
Airliner		1,056
TufTrac		1,084
Primax		1,072
Neway		1,072
HFF - HEIGHT	FROM FRAME	
Day cab standa	rd roof	2,042
Day cab low tre	ench style roof	2,003
36" low trench	style roof	2,012
36", 48" & 60"	mid style roof	2,460
Mid roof style s	leeper air kit	625

➤ CAB

STD	Steel reinforced day cab w/- aluminium roof 2,865 mm/113" BBC
OPT	Low trench style roof steel reinforced day cab w/- composite roof
OPT	SLEEPERS 36" low trench style roof 36" mid style roof 48" mid style roof 60" mid style roof Additional roof fairing and side fairings - aerodynamic devices available

> AIR INTAKE

STD	Side of bonnet air intake with engine mounted high capacity air cleaner and passive pre-cleaner
	Dual air intake through hood mounted snorkles with RAM scoops, engine mounted high capacity air cleaner and dual passive pre-cleaners

> ENGINE

STD	Detroit DD13 Gen 5 450 hp, 1,550 lb-ft
OPT	Detroit DD13 Gen 5 470-525 hp, 1,650-1,850 lb-ft
	Detroit DD16 GHG21 500-600 hp, 1,850-2,050 lb-ft

> EXHAUST

STD Horizontal ATS with LF	B-pillar mounted vertical tailpipe
OPT Horizontal ATS with rig	sht hand horizontal tailpipe
Horizontal ATS with du	al cab mounted vertical tailpipes
Horizontal ATS with du	al frame mounted vertical tailpipes
Horizontal ATS with du	ial cab mounted vertical tailpipes

> TRANSMISSION - AUTOMATED MANUAL

STD	Detroit DT12 OV 12 speed overdrive 1,550 lb-ft
0PT	Detroit DT12 OV 12 speed overdrive 1,650 lb-ft to 1,850 lb-ft
	Detroit DT12 OVX 12 speed overdrive 1,850 lb-ft to 2,050 lb-ft

> TRANSMISSION - MANUAL

0PT	Eaton RTLO-16918B 1,650 lb-ft
	Eaton RTLO-18918B 1,850 lb-ft
	Eaton RTLO-20918B 2,050 lb-ft
	Eaton RTLO-22918B 2,250 lb-ft

> FRONT AXLE

STD	Meritor 6.6 t FG941 3.5" drop single front axle
0PT	Detroit 7.3 t DA-F 3.5" drop single front axle

> FRONT SUSPENSION

STD	Taper leaf springs 6.6 t capacity - FG941
0PT	Taper leaf springs 7.3 t capacity - Detroit DA-F



SPECIFICATIONS



> REAR AXLE

STD Meritor MX-40-14XGP 18.1 t GAWR tandem
OPT Meritor MX44-14XGP 19.9 t GAWR tandem
Meritor RT46-160GP 20.1 t GAWR tandem
Meritor RT50-160GP 22.7 t GAWR tandem
Meritor RT52-185G 23.6 t GAWR tandem

Dana D46-172P 20.1 GAWR tandem

> REAR SUSPENSION

STD | Airliner 20.9 t GAWR air bag tandem

OPT | Airliner 18.1 t GAWR air bag tandem

TufTrac Gen 2 18.1 t - 23.5 t GAWR mechanical tandem TufTrac Gen 2 Comfort Ride 18.1 t - 20.9 t GAWR mechanical tandem

Hendrickson Primax EX 20.9 t GAWR air bag tandem Neway ADZ-252 23.5 t GAWR air bag tandem Neway AD-260 27.2 t GAWR air bag tandem

> BRAKES

STD Bendix disc
OPT Meritor drum

> UPFIT EFFICIENCY SYSTEMS

STD Advanced multiplexed electrical system for easy truck equipment interface:

• Hard wired dash mounted auxiliary switches

OPT Manufacturer body builder interface, programming and power access Auxiliary in-cab or sleeper mounted e-vault available, which houses:

- QuickFit programmable controllers
- QuickFit interface connectors
- TEM-specific power distribution module
- High-current power access

≫ WHEELS

STD Aluminium disc 10 stud
OPT Steel disc 10 stud
Standard, polished or Dura-Bright wheel finish available on
Aluminium wheels

> FUEL/HYDRAULIC & COMBINATION TANKS

STD Round 635 mm diameter 227 L to 567 L*
Square (LCS) 735 mm x 700 mm 320 L to 775 L
*Various fuel and hydraulic tank combinations available

> SAFETY SYSTEMS

STD | With Detroit DT12 transmissions:

Detroit Assurance® Safety Systems including:

- Active Brake Assist 5
- · Adaptive cruise control to 0 kms with adj headway
- Side guard assist (OPT)
- Lane departure warning
- Automatic wipers/headlamps
- Intelligent high beam control
- Brake hold
- Electronic stability control
- Anti-lock braking system
- Detroit Connect and Virtual Technician platform hardware
- Detroit Connect Safety Event Viewer package
- Pre-Trip Inspection feature for exterior lamps
- Alarm for door open, park brake not set

OPT | With manual transmissions all of the above except:

- Standard (adaptive) cruise control
- No brake hold
- Optional lane departure warning
- Optional side guard assist

DRIVER INFORMATION MODULE

STD | Premium instrument cluster with 125 mm TFT colour display

OPT Digital dash displays with 300 mm centre panel cluster and 250 mm B-panel infotainment display

> DRIVERS SEATS

STD | ISRI high back air suspension seat with integrated 3 point seat belt OPT | Rolltek Gen 2 air bag integrated into std ISRI seat

ISRI Premium 2.0 high back air suspension seat with swivel base and non-integrated seat belts

> PASSENGER SEATS

STD | Sears tool box high back non suspension seat

OPT | ISRI high back air suspension seat with integrated 3 point seat belt | ISRI Premium 2.0 high back air suspension seat with swivel base | and non-integrated seat belts

Battery box mid back non suspension seat

> PAINT

STD | Single colour cab and single colour chassis Cab - one colour basecoat/clearcoat, Chassis - one colour basecoat/clearcoat

OPT Up to 4 colours. Base coat/Clearcoat solid colour, metallic or pearl

