




# **WESTERN STAR 47X**



CONFIGURATIONS	
8 X 4 TWIN STEER	
GCM	
UPTO 72.5 TONNE	GCM
	мм
BA - BUMPER TO AXLE	
	1,180
	1,968
BBC - BUMPER TO BACK OF CAB	
	2,835
RRF - REAR FRAME HEIGHT - UNLADEN	
	1,056
HFF - HEIGHT FROM FRAME	
	1,942
	8 X 4 TWIN STEER GCM UP TO 72.5 TONNE LE ACK OF CAB HEIGHT - UNLADEN

#### > CAB

STD | Steel reinforced day cab w/- aluminium roof 2,835 mm/111.6" BBC

OPT | Low trench style roof steel reinforced day cab w/- composite roof

# **> AIR INTAKE**

STD | Single side of hood air intake with engine mounted high capacity air cleaner and passive precleaner

# **> ENGINE**

STD Detroit DD13 Gen 5 450 hp, 1,550 lb-ft
Detroit - Jacobs Compression brake

OPT Detroit DD13 Gen 5 470 hp, 1,650 lb-ft
Detroit DD13 Gen 5 505 hp, 1,850 lb-ft
Detroit DD13 Gen 5 525hp, 1,850 lb-ft

# > EXHAUST

STD | RH mid frame mounted ATD with RH horizontal tailpipe

## > TRANSMISSION - AUTOMATIC

STD Detroit DT12 AMT 1550 - OV 12 Speed transmission
OPT Detroit DT12 AMT 1650 - OV 12 Speed transmission
Detroit DT12 AMT 1750 - OV 12 Speed transmission
Detroit DT12 AMT 1850 - OV 12 Speed transmission

#### > TRANSMISSION - MANUAL

OPT Eaton RTLO-16918B 1,650 lb-ft Eaton RTLO-18918B 1,850 lb-ft Eaton RTLO-20918B 2,050 lb-ft

# > FRONT AXLE

STD | Meritor MFS-14-143A 13.3t 3.5" drop tandem front axles

# > FRONT SUSPENSION

STD | Tandem taperleaf spring 13.2 t capacity, load sharing

# **> REAR AXLE**

STD Meritor MT44-14X 19.95 t GAWR tandem
OPT Meritor MT40-14XGP 18.1 t GAWR tandem
Meritor RT-46-160GP 20.9 t GAER tandem

# > REAR SUSPENSION

STD Airliner 18.1 t GAWR air bag tandem
OPT Airliner 20.9 t GAWR air bag tandem

#### **≫ BRAKES**

STD Bendix Air Disc



# **8X4 DD13 SPECIFICATIONS**



#### > UPFIT EFFICIENCY SYSTEMS

STD • Advanced multiplexed electrical system for easy truck equipment interface:

- Hard wired dash mounted auxiliary switches
- Prep for customer supplied PTO
- Prep for remote Engine control with park brake interlock
- RP1226 telematics connector to J1939 network for customer fit telematics

OPT • Manufacturer body builder interface, programming and power access Auxiliary in-cab or sleeper mounted e-vault available, which houses:

- QuickFit programmable controllers
- QuickFit interface connectors
- TEM-specific power distribution module
- High-current power access

# > ELECTRICAL SYSTEM

STD | 12 Volt System | 160 amp Alternator | Detroit Mitsubishi 12V Mod 31 755-DP60

#### **> SAFETY SYSTEMS**

STD With Detroit DD13 Engines and Detroit DT12 Transmissions: Detroit Assurance® Safety Systems including:

- Active Brake Assist 5
- Adaptive cruise control to 0 kms with adj headway
- Lane departure warning
- Automatic wipers/headlamps
- Intelligent high beam control
- Brake hold
- Electronic stability control
- Anti-lock braking system
- Detroit Connect and Virtual Technician platform hardware
- Detroit Connect Safety Event Viewer package
- Pre-Trip Inspection feature for exterior lamps
- Alarm for door open, park brake not set

OPT | With manual transmissions all of the above except:

- Standard (adaptive) cruise control
- No brake hold
- Optional lane departure warning
- Optional side guard assist

#### > SECURITY

OPT Remote keyless entry

# > DRIVER INFORMATION MODULE

STD Premium instrument cluster with 125 mm TFT colour display with controls on steering wheel

OPT Digital dash displays with 300 mm centre panel cluster and 250 mm B-panel infotainment display
DT12 transmission only

#### DRIVERS SEATS

STD | ISRI high back air suspension seat with integrated 3 point seat belt

OPT Rolltek Gen 2 air bag integrated into std ISRI seat ISRI Premium 2.0 high back air suspension seat with swivel base and non-integrated seat belts

#### > PASSENGER SEATS

STD | Sears tool box high back non suspension seat

OPT ISRI high back air suspension seat with integrated 3 point seat belt ISRI Premium 2.0 high back air suspension seat with swivel base and non-integrated seat belts

Battery box mid back non suspension seat

# **≫ WHEELS**

STD No front wheel polishing
OPT Polished aluminium disc 10 stud
Dura-Bright wheel finish

#### > FUEL TANKS

STD Round 635 mm diameter 227 L to 567 L\*

OPT | Square (LCS) 735 mm x 700 mm 320 L to 775 L

\*Various fuel and hydraulic tank combinations available

#### **DEFTANKS**

STD 49L diesel exhaust fluid tank

OPT 87L diesel exhaust fluid tank

# **PAINT**

STD | Single colour cab. Cab - one colour basecoat/clearcoat, Chassis - one colour basecoat/clearcoat

OPT Up to 4 colours. Base coat/Clearcoat solid colour, metallic or pearl



No matter where you are, we can get you going – 24 hour road assistance.

1800 247 WSTAR 1800 247 97827



## PENSKE AUSTRALIA • 72 FORMATION STREET WACOL QLD 4076 • PHONE (07) 3271 7777